



Designation	Bearing with retaining cap Designation	Dimensions (mm)								
		Fw	D	D1 max.	D2 max.	C	C1	C2	dw	r min.
NKX10 TV	NKX10 Z TV	10	19	24,1	25,2	23	9	6,5	10	0,3
NKX12	NKX12 Z	12	21	26,1	27,2	23	9	6,5	12	0,3
NKX15	NKX15 Z	15	24	28,1	29,2	23	9	6,5	15	0,3
NKX17	NKX17 Z	17	26	30,1	31,2	25	9	8	17	0,3
NKX20	NKX20 Z	20	30	35,1	36,2	30	10	10,5	20	0,3
NKX25	NKX25 Z	25	37	42,1	43,2	30	11	9,5	25	0,6
www.mybearing.eu										
NKX30	NKX30 Z	30	42	47,1	48,2	30	11	9,5	30	0,6
NKX35	NKX35 Z	35	47	52,1	53,2	30	12	9	35	0,6
NKX40	NKX40 Z	40	52	60,1	61,2	32	13	10	40	0,6
NKX45	NKX45 Z	45	58	65,2	66,5	32	14	9	45	0,6
NKX50	NKX50 Z	50	62	70,2	71,5	35	14	10	50	0,6
www.mybearing.eu										
NKX60	NKX60 Z	60	72	85,2	86,5	40	17	12	60	1
NKX70	NKX70 Z	70	85	95,2	96,5	40	18	11	70	1



sales@icbe.net

www.mybearing.eu

www.icbe.net

www.icbe.de

Alle Angaben wurden sorgfältig geprüft, dennoch können wir für Fehler keine Haftung übernehmen

(C) 2015 ICBE InterContinental Bearing Equipment GMBH

www.mybearing.eu